Printing date 19.12.2022

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Antistatic-Zusatz
- · **UFI:** 5SC0-H0AP-2005-F34K
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Additional component
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pramol-Chemie AG

Industriestrasse 3

CH-9602 Bazenheid/SG

Tel +41 71 931 70 30

Fax +41 71 931 44 54

· Further information obtainable from:

Abteilung für Produktsicherheit

info@pramol.com

Tel. 071 931 70 30

· 1.4 Emergency telephone number:

Centre suisse d'information toxicologique, Zurich

+41 (0)44 251 51 51 ou 145 (depuis la Suisse)

Schweizerisches Toxikologisches Informationszentrum, Zürich

+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145

Centro Svizzero d'informazione tossicologica

+41 (0)44 251 51 51 o dalla Svizzera: Tel 145

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Acute 1 H400 Very toxic to aquatic life.



Acute Tox. 4

H302 Harmful if swallowed.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS05, GHS07, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling:

didecyldimethylammonium chloride

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Revision: 19.12.2022

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

· Precautionary statements

P102 Keep out of reach of children.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

ſ	· Dangerous components:				
Γ		didecyldimethylammonium chloride	25-50%		
	EINECS: 230-525-2	🔗 Skin Corr. 1B, H314; 🕸 Aquatic Acute 1, H400; Aquatic Chronic			
	Reg.nr.: 01-2119945987-15	Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302			
ſ	CAS: 67-63-0	propan-2-ol	20%		
	EINECS: 200-661-7	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336			
	Reg.nr.: 01-2119457558-25	* * * * *			

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with l	limit values tha	t require moi	nitoring at th	e workplace:
----------------------	------------------	---------------	----------------	--------------

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· DNELs

7173-51-5 didecyldimethylammonium chloride

Dermal DNEL long term systemic effects 8.6 mg/kg bw/day (workers)
Inhalative DNEL long term systemic effects 18.2 mg/m3 (workers)

· PNECs

7173-51-5 didecyldimethylammonium chloride

PNEC 595 mg/l (sewage plant)
PNEC aqua 2 mg/l (fresh water)
0.0002 mg/l (sea water)

PNEC sediment 2.82 mg/kg (fresh water)

(Contd. on page 4)

Printing date 19.12.2022 *Version number 4 (replaces version 3)* Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 3)

282 mg/kg (sea water) 1.4 mg/kg (ground)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

PNEC ground

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



Protective gloves

- · Material of gloves Rubber gloves
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

· Eye/face protection Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Light yellow · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

0 °C range

Not applicable. · Flammability

· Lower and upper explosion limit

2 Vol % · Lower: 12 Vol % · Upper: Not applicable. · Flash point: 425 °C

· Ignition temperature:

Not determined. · Decomposition temperature:

· pH at 20 °C

· Viscosity:

Not determined. · Kinematic viscosity Not determined. · Dynamic:

·Solubility

Fully miscible. · Partition coefficient n-octanol/water (log value) Not determined. 43 hPa

· Vapour pressure at 20 °C: Density and/or relative density

· Density at 20 °C: $0.906 \, \text{g/cm}^3$ · Relative density Not determined. · Vapour density Not determined.

(Contd. on page 5)

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

· Organic solvents: 20.0 %
· Water: 30.0 %

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Void · Flammable solids · Self-reactive substances and mixtures Void Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures · Substances and mixtures, which emit flammable Void gases in contact with water Void · Oxidising liquids Void · Oxidising solids

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Organic peroxides

· Corrosive to metals

· Desensitised explosives

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if swallowed.

· LD/LC50 values relevant for classification:

7173-51-5 didecyldimethylammonium chloride

 Oral
 LD50
 238 mg/kg (Rat)

 Dermal
 LD50
 3,342 mg/kg (Rabbit)

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 6)

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 5)

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
7173-51-5 d	idecyldimethylammonium chloride	
NOEC	530 mg/l (Chironomus sp.) (OECD 218, 28d)	
	32 mg/l (Danio rerio) (OECD 210, 34 d)	
	10 mg/l (Daphnia magna) (OECD 211, 21d)	
	≥1,000 mg/l (Eisenia fetida) (OECD 207, 14d)	
LC50 (96h)	0.19 mg/l (Pimephales promelas) (US-EPA)	
EC50	62 mg/l (Daphnia magna) (EPA-FIFRA, 48h)	
	26 mg/l (Pseudokirchneriella subcapitata) (OECD-201, 96h)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

 $Do \ not \ allow \ product \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Very toxic for aquatic organisms

GB

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1760
14.2 UN proper shipping name ADR	1760 CORROSIVE LIQUID, N.O (didecyldimethylammonium chlorid ENVIRONMENTALLY HAZARDOUS
IMDG, IATA	CORROSIVE $LIQUID$, $N.O$. (didecyldimethylammonium chloride)
14.3 Transport hazard class(es)	
ADR	
Class	8 Corrosive substances.
Label	8
IMDG, IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80 E 4 S B
EMS Number: Stowage Category	F-A,S-B A
Stowage Code	SW2 Clear of living quarters.

(Contd. on page 8)

Printing date 19.12.2022 Version number 4 (replaces version 3) Revision: 19.12.2022

Trade name: Antistatic-Zusatz

	(Contd. of page
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S
<u> </u>	(DIDECYLDIMETHYLAMMONIUM CHLORIDE), 8
	III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Regulation (EC) No 648/2004 on detergents / Labelling for contents

 cationic surfactants

 ≥30%

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3) Printing date 19.12.2022 Revision: 19.12.2022

Trade name: Antistatic-Zusatz

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation — Category 1 Eye Irrit. 2: Serious eye damage/eye irritation — Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.