Printing date 20.12.2022

Version number 20 (replaces version 19)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CleanTEX liquide 79
- · **UFI:** TFG3-E0HN-X00D-9G97
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Textile auxiliary
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pramol-Chemie AG

Industriestrasse 3

CH-9602 Bazenheid/SG

Tel +41 71 931 70 30

Fax +41 71 931 44 54

· Further information obtainable from:

Abteilung für Produktsicherheit

info@pramol.com

Tel. 071 931 70 30

· 1.4 Emergency telephone number:

Centre suisse d'information toxicologique, Zurich

+41 (0)44 251 51 51 ou 145 (depuis la Suisse)

Schweizerisches Toxikologisches Informationszentrum, Zürich

+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145

Centro Svizzero d'informazione tossicologica

+41 (0)44 251 51 51 o dalla Svizzera: Tel 145

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame over circle

Ox. Liq. 2 H272 May intensify fire; oxidiser.



corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS03, GHS05, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

hydrogen peroxide solution

peracetic acid

acetic acid

(Contd. on page 2)

Revision: 20.12.2022

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 1)

· Hazard statements

H272 May intensify fire; oxidiser. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P102 Keep out of reach of children.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7722-84-1	hydrogen peroxide solution	20-25%
EINECS: 231-765-0	🕲 Ox. Liq. 1, H271; 🍪 Skin Corr. 1A, H314; 🔱 Acute Tox. 4,	
Reg.nr.: 01-2119485845-22	H302; Acute Tox. 4, H332	
	Specific concentration limits: Ox. Liq. 1; H271: C ≥ 70 %	
	Ox. Liq. 2; H272: $50 \% \le C < 70 \%$	
	Skin Corr. 1A; H314: C ≥ 70 %	
	Skin Corr. 1B; H314: 50 % ≤ C < 70 %	
	Skin Irrit. 2; H315: 35 % ≤ C < 50 %	
	Eye Dam. 1; H318: C ≥ 8 %	
	Eye Irrit. 2; H319: 5 % ≤ C < 8 %	
	STOT SE 3; C ≥ 35 %	
CAS: 64-19-7	acetic acid	10-20%
EINECS: 200-580-7 Reg.nr.: 01-2119475328-30	Flam. Liq. 3, H226; Skin Corr. IA, H314; Acute Tox. 4, H312; Acute Tox. 4, H332	
	Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 %	
	Skin Corr. 1B; H314: 25 % ≤ C < 90 %	
	Skin Irrit. 2; H315: 10 % ≤ C < 25 %	
	Eye Irrit. 2; H319: 10 % ≤ C < 25 %	
CAS: 79-21-0	peracetic acid	≥2.5-<5%
EINECS: 201-186-8	🐠 Flam. Liq. 3, H226; Org. Perox. D, H242; 🕎 Skin Corr. 1A,	
Reg.nr.: 01-2119531330-56	H314; 🕸 Aquatic Acute 1, H400; 🕦 Acute Tox. 4, H302; Acute	
	Tox. 4, H312; Acute Tox. 4, H332	
	Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

-GB

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 2)

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: aluminium.
- Information about storage in one common storage facility: Store away from flammable substances.
- · Further information about storage conditions:

Protect from exposure to the light.

(Contd. on page 4)

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 3)

Keep container tightly sealed.

· Storage class: 5.1 B

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace	e:
7722-84-1 hydrogen peroxide solution	

WEL Short-term value: 2.8 mg/m³, 2 ppm Long-term value: 1.4 mg/m³, 1 ppm

#### 64-19-7 acetic acid

WEL Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm

#### · DNELs

#### 7722-84-1 hydrogen peroxide solution

Inhalative DNEL long term systemic effects 1.4 mg/m3 (workers)

DNEL short term local effects 1.93 mg/m3 (general population)
3 mg/m3 (workers)

DNEL long term local effects 0.21 mg/m3 (general population)

#### · PNECs

#### 7722-84-1 hydrogen peroxide solution

//22-84-1 nyarogen peroxiae solution	
PNEC	0.0138 mg/l (intermittent release)
	4.66 mg/l (sewage plant)
PNEC aqua	0.0126 mg/l (fresh water)
	0.0126 mg/l (sea water)
PNEC sediment	0.47 mg/kg (fresh water)
	0.47 mg/kg (sea water)
PNEC ground	0.0023 mg/kg (ground)

1.4 mg/m3 (workers)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A / ABEK

### · Hand protection



Protective gloves

EN 374

· **Material of gloves** Nitrile rubber, NBR

(Contd. on page 5)

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 4)

Butyl rubber, BR

Chloroprene rubber, CR

Recommended thickness of the material:  $\geq 0.5$  mm

· Penetration time of glove material

≥8h

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

EN166

· Body protection:

Protective work clothing

Impervious protective clothing

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Colourless
Pungent
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range 100 °C

· Flammability Not applicable.

Lower and upper explosion limit

Lower: 4 Vol %
Upper: 17 Vol %
Flash point: Not applicable.
Ignition temperature: 485 °C

• **Decomposition temperature:** Not determined.

• pH at 20 °C 2.5

· Viscosity:

· Kinematic viscosity at 20 °C 9 s (ISO 4 mm)
· Dynamic: Not determined.

Solubility

• water: Fully miscible.
• Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 23 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

Organic solvents: 14.0 %

(Contd. on page 6)

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

	(Cor	ntd. of page
Water:	58.6 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard c	elasses	
Explosives	Void	
1	Void	
Flammable gases	Void	
ŭ	Void	
Aerosols	Void	
	Void	
Oxidising gases	Void	
	Void	
Gases under pressure	Void	
•	Void	
Flammable liquids	Void	
•	Void	
Flammable solids	Void	
	Void	
Self-reactive substances and mixtures	Void	
	Void	
Pyrophoric liquids	Void	
	Void	
Pyrophoric solids	Void	
<i>V</i> 1	Void	
Self-heating substances and mixtures	Void	
, ,	Void	
Substances and mixtures, which emit flamme	able	
gases in contact with water	Void	
	Void	
Oxidising liquids	May intensify fire; oxidiser.	
0 1	Void	
Oxidising solids	Void	
	Void	
Organic peroxides	Void	
•	Void	
Corrosive to metals	Void	
	Void	
Desensitised explosives	Void	
1	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if swallowed.
- · Skin corrosion/irritation Causes severe skin burns and eye damage.

(Contd. on page 7)

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 6)

- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN3149
· 14.2 UN proper shipping name	
$\cdot ADR$	3149 HYDROGEN PEROXIDE AND PEROXYACETI
	ACID MIXTURE, STABILIZED
· IMDG, IATA	HYDROGEN PEROXIDE AND PEROXYACETIC ACL
	MIXTURE, STABILIZED

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 7) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 5.1 Oxidising substances. ·Label 5.1 + 8 $\cdot$  IMDG · Class 5.1 Oxidising substances. ·Label 5.1/8  $\cdot$  IATA 5.1 Oxidising substances. · Class · Label 5.1 (8) · 14.4 Packing group II· ADR, IMDG, IATA · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Oxidising substances. · Hazard identification number (Kemler code): 58 D· Stowage Category · Stowage Code SW1 Protected from sources of heat. SG16 Stow "separated from" class 4.1 SG59 Stow "separated from" SGG14-permanganates · Segregation Code SG72 See 7.2.6.3.2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information:  $\cdot ADR$ · Limited quantities (LQ) Code: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code E· Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

Printing date 20.12.2022 Version number 20 (replaces version 19) Revision: 20.12.2022

Trade name: CleanTEX liquide 79

(Contd. of page 8)

· UN "Model Regulation":

UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED, 5.1

(8), II

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P8 OXIDISING LIQUIDS AND SOLIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Regulation (EC) No 648/2004 on detergents / Labelling for contents

oxygen-based bleaching agents

≥15 - <30%

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H271 May cause fire or explosion; strong oxidiser.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Ox. Liq. 1: Oxidizing liquids - Category 1

Ox. Liq. 2: Oxidizing liquids – Category 2

Org. Perox. D: Organic peroxides - Type C/D

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

\* Data compared to the previous version altered.

GB