Printing date 19.12.2022

Version number 33 (replaces version 32)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Pramotec GC
- · **UFI:** FVJ1-50H5-C00X-7JVF
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Protective impregnation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pramol-Chemie AG

Industriestrasse 3

CH-9602 Bazenheid/SG

Tel +41 71 931 70 30

Fax +41 71 931 44 54

· Further information obtainable from:

Abteilung für Produktsicherheit

info@pramol.com

Tel. 071 931 70 30

· 1.4 Emergency telephone number:

Centre suisse d'information toxicologique, Zurich

+41 (0)44 251 51 51 ou 145 (depuis la Suisse)

Schweizerisches Toxikologisches Informationszentrum, Zürich

+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145

Centro Svizzero d'informazione tossicologica

+41 (0)44 251 51 51 o dalla Svizzera: Tel 145

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

(Contd. on page 2)

Revision: 19.12.2022

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Results of PBT and vPvB assessment

Results of 1 D1 time v1 vD tissessment
· PBT:
541-02-6 decamethylcyclopentasiloxane
· vPvB:
541-02-6 decamethylcyclopentasiloxane

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0	propan-2-ol	50-100%
EINECS: 200-661-7	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25	• • • • • •	
CAS: 541-02-6	decamethylcyclopentasiloxane	5-10%
EINECS: 208-764-9	Non-classified vPvB substance.	
Reg.nr.: 01-2119511367-43	Non-classified PBT substance.	
	Substance identified as having endocrine disrupting properties (II).	

·SVHC

541-02-6 decamethylcyclopentasiloxane

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workpl	lace:
---	-------

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· DNELs

67-63-0 propan-2-ol

_		
Oral	DNEL long term systemic effects	26 mg/kg bw/day (general population)
Dermal	DNEL long term systemic effects	319 mg/kg bw/day (general population)
		888 mg/kg bw/day (workers)
Inhalative	DNEL long term systemic effects	89 mg/m3 (general population)
		500 mg/m3 (workers)

· PNECs

67-63-0 propan-2-ol

07-03-0 propun-2-01	
PNEC	140.9 mg/l (intermittent release)
	2,251 mg/l (sewage plant)
-	140.9 mg/l (fresh water)
	140.9 mg/l (sea water)
$PNEC\ sediment$	552 mg/kg (fresh water)
	552 mg/kg (sea water)
PNEC ground	28 mg/kg (ground)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 3)

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



Protective gloves

FN 374

· Material of gloves

Rubber gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

EN166

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Odour threshold:
Fluid
Colourless
Alcohol-like
Not determined.

· Melting point/freezing point: <0 °C

Boiling point or initial boiling point and boiling

range 82 °C

· Flammability Not applicable.

· Lower and upper explosion limit

 Lower:
 0.5 Vol %

 · Upper:
 12 Vol %

 · Flash point:
 13 °C

 · Ignition temperature:
 385 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

 $\cdot \textit{Solubility}$

• water: Easily soluble. • Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 43 hPa

· Density and/or relative density

• **Density at 20 °C:** 0.806 g/cm³

(Contd. on page 5)

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

	(Contd. of page
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of healt	th and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent separation test:	
Organic solvents:	88.8 %
Water:	0.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard c	classes
Explosives	Void
•	Void
Flammable gases	Void
g	Void
Aerosols	Void
	Void
Oxidising gases	Void
8.8	Void
Gases under pressure	Void
1	Void
Flammable liquids	Highly flammable liquid and vapour.
1	Void
Flammable solids	Void
	Void
Self-reactive substances and mixtures	Void
,	Void
Pyrophoric liquids	Void
	Void
Pyrophoric solids	Void
•	Void
Self-heating substances and mixtures	Void
	Void
Substances and mixtures, which emit flamme	
gases in contact with water	Void
	Void
Oxidising liquids	Void
	Void
Oxidising solids	Void
	Void
Organic peroxides	Void
- •	Void
Corrosive to metals	Void
	Void
Desensitised explosives	Void
<u>.</u>	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:		
67-63-0	propai	n-2-ol	
Oral	<i>LD50</i>	5,280 mg/kg (Rat)	
Dermal	LD50	17,600 mg/kg (Rabbit)	

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

541-02-6 decamethylcyclopentasiloxane

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

67-63-0 propan-2-ol

EC50 (48h) 13,299 mg/l (Daphnia magna)

LC50 (96h) 9,640 mg/l (Pimephales promelas)

- 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT:

541-02-6 decamethylcyclopentasiloxane

· vPvB:

541-02-6 decamethylcyclopentasiloxane

- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR IMDG, IATA	1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANO (ISOPROPYL ALCOHOL)) FLAMMABLE LIQUID, N.O.S. (ISOPROPANO (ISOPROPYL ALCOHOL))
14.3 Transport hazard class(es)	(Isel Nel 12 illeeileg))
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O. (ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II

Printing date 19.12.2022 Version number 33 (replaces version 32) Revision: 19.12.2022

Trade name: Pramotec GC

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · National regulations:
- · Substances of very high concern (SVHC) according to UK REACH

541-02-6 decamethylcyclopentasiloxane

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB