Printing date 19.12.2022

Version number 11 (replaces version 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: graffiti-ex SR
- · UFI: R0W2-M04A-3000-230C
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Alkaline cleaner/ detergent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Pramol-Chemie AG

Industriestrasse 3

CH-9602 Bazenheid/SG

Tel +41 71 931 70 30

Fax +41 71 931 44 54

· Further information obtainable from:

Abteilung für Produktsicherheit

info@pramol.com

Tel. 071 931 70 30

· 1.4 Emergency telephone number:

Centre suisse d'information toxicologique, Zurich

+41 (0)44 251 51 51 ou 145 (depuis la Suisse)

Schweizerisches Toxikologisches Informationszentrum, Zürich

+41 (0)44 251 51 51 oder aus der Schweiz: Tel 145

Centro Svizzero d'informazione tossicologica

+41 (0)44 251 51 51 o dalla Svizzera: Tel 145

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P102 Keep out of reach of children.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

Revision: 19.12.2022

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol •• Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	10-20%
CAS: 141-43-5 EINECS: 205-483-3 Reg.nr.: 01-2119486455-28	2-aminoethanol Skin Corr. 1B, H314;	
EINECS: 215-181-3	potassium hydroxide \Leftrightarrow Skin Corr. IA, H314; \Leftrightarrow Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1A; H314: $C \ge 5$ % Skin Corr. 1B; H314: 2 % $\le C < 5$ % Skin Irrit. 2; H315: 0.5 % $\le C < 2$ % Eye Irrit. 2; H319: 0.5 % $\le C < 2$ %	5-10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

141-43-5 2-aminoethanol

WEL Short-term value: 7.6 mg/m³, 3 ppm

Long-term value: 2.5 mg/m³, 1 ppm

Sk

1310-58-3 potassium hydroxide

WEL Short-term value: 2 mg/m³

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

(Contd. on page 4)

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



Protective gloves

- · Material of gloves Rubber gloves
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Alkaline resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Light yellow
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 100 °C

· Flammability Not applicable.

· Lower and upper explosion limit

 · Lower:
 1.1 Vol %

 · Upper:
 12.2 Vol %

 · Flash point:
 93 °C

 · Ignition temperature:
 190 °C

• **Decomposition temperature:** Not determined.

· pH at 20 °C 13

· Viscosity:

• Kinematic viscosity at 20 °C 10 s (DIN 53211/4)
• Dynamic: Not determined.

·Solubility

water: Fully miscible.
Partition coefficient n-octanol/water (log value)
Vapour pressure at 20 °C: 23 hPa

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

(Contd. on page 5)

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

• Organic solvents: 80.0 %
 • Water: 10.0 %
 • VOC (EC) 80.00 %
 • Solids content: 10.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void Void · Oxidising gases Void · Gases under pressure · Flammable liquids Void Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Corrosive to metals

· Desensitised explosives

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if inhaled.

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 5)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN3266

(Contd. on page 7)

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

	(Contd. of page
14.2 UN proper shipping name ADR	3266 CORROSIVE LIQUID, BASIC, INORGANIC N.O.S. (POTASSIUM HYDROXIDE)
IMDG, IATA	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80 E. A.G. P.
EMS Number:	F-A,S-B
Segregation groups Stowage Category	(SGG18) Alkalis A
Stowage Category Stowage Code	SW2 Clear of living quarters.
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according to IM.	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- · · · ~	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3266 CORROSIVE LIQUID, BASIC, INORGANIO
	N.O.S. (POTASSIUM HYDROXIDE), 8, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GR

Printing date 19.12.2022 Version number 11 (replaces version 10) Revision: 19.12.2022

Trade name: graffiti-ex SR

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

-GB