
# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Revision: 20.12.2022



Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Revision: 20.12.2022

Trade name: tapi-foam

· vPvB: Not applicable.

(Contd. of page 1)

# **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	e, pure am. Gas 1A, H220; ⊗ Acute Tox. 3, H331; Press. Gas (Comp.),	10-20%
Reg.nr.: 01-2119471991-29 🐼 F	tha (petroleum), heavy alkylate am. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚸 Aquatic Chronic 2, , EUH066	5-10%
CAS: 74-98-6 propo EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	une am. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-5%
EINECS: 288-330-3	nic acids, C13-17-sec-alkane, sodium salts cin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

# **SECTION 6:** Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)

GR

Page 3/8

\*

\*

\*

Safety data sheet according to 1907/2006/EC, Article 31

Version number 31 (replaces version 30)

Printing date 20.12.2022

Revision: 20.12.2022

### Trade name: tapi-foam

(Contd. of page 2)

<b>SECTION 7: Handling a</b>	nd storage
7.1 Precautions for safe handl	ing
Ensure good ventilation/exhaus	
Open and handle receptacle wi	
Information about fire - and e.	
	ne or any incandescent material.
Keep ignition sources away - D	
Protect against electrostatic ch	
	from sunlight and do not expose to temperatures exceeding 50°C, i.e. electr
lights. Do not pierce or burn, e	
	e, including any incompatibilities
Storage:	
Requirements to be met by stor	rerooms and receptacles:
<i>Store in a cool location.</i>	
	storing packagings with pressurised containers.
Further information about storage in a	one common storage facility: Not required.
Keep container tightly sealed.	inge communities.
Do not seal receptacle gas tigh	t
Store in cool, dry conditions in	
Protect from heat and direct su	
Storage class: 2 B	
	her relevant information available.
SECTION 8: Exposure co 8.1 Control parameters	
8.1 Control parameters	hat require monitoring at the workplace:
8.1 Control parameters Ingredients with limit values th 106-97-8 butane, pure	hat require monitoring at the workplace:
• 8.1 Control parameters • Ingredients with limit values th 106-97-8 butane, pure WEL Short-term value: 1810 n	hat require monitoring at the workplace: ng/m³, 750 ppm
• 8.1 Control parameters • Ingredients with limit values th 106-97-8 butane, pure WEL Short-term value: 1810 n Long-term value: 1450 n	hat require monitoring at the workplace: ng/m³, 750 ppm ng/m³, 600 ppm
• 8.1 Control parameters • Ingredients with limit values th 106-97-8 butane, pure WEL Short-term value: 1810 n	hat require monitoring at the workplace: ng/m³, 750 ppm ng/m³, 600 ppm
8.1 Control parameters         Ingredients with limit values th         106-97-8 butane, pure         WEL       Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%)	hat require monitoring at the workplace: ng/m³, 750 ppm ng/m³, 600 ppm
8.1 Control parameters         Ingredients with limit values th         106-97-8 butane, pure         WEL       Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%)	hat require monitoring at the workplace: ng/m³, 750 ppm ng/m³, 600 ppm of buta-1.3-diene)
8.1 Control parameters         Ingredients with limit values th         106-97-8 butane, pure         WEL       Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%)         Additional information: The line         8.2 Exposure controls         Appropriate engineering control	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. <b>ols</b> No further data; see item 7.
8.1 Control parameters     Ingredients with limit values th     106-97-8 butane, pure     WEL Short-term value: 1810 n     Long-term value: 1450 n     Carc (if more than 0.1%     Additional information: The li.     8.2 Exposure controls     Appropriate engineering contrel     Individual protection measure	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment
8.1 Control parameters     Ingredients with limit values th     106-97-8 butane, pure     WEL Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%     Additional information: The li.     8.2 Exposure controls     Appropriate engineering contre     Individual protection measure     General protective and hygient	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. rols No further data; see item 7. s, such as personal protective equipment ic measures:
8.1 Control parameters         Ingredients with limit values th         106-97-8 butane, pure         WEL       Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%         • Additional information: The li.         • 8.2 Exposure controls         • Appropriate engineering contr         • Individual protection measure.         • General protective and hygient.         Wash hands before breaks and	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work.
8.1 Control parameters         Ingredients with limit values th         106-97-8 butane, pure         WEL       Short-term value: 1810 n         Long-term value: 1450 n         Carc (if more than 0.1%         • Additional information: The li.         • 8.2 Exposure controls         • Appropriate engineering contr         • Individual protection measure         • General protective and hygient         Wash hands before breaks and         Do not inhale gases / fumes / ac	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols.
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 nn Long-term value: 1450 nn Carc (if more than 0.1%)</li> <li>Additional information: The line</li> <li>8.2 Exposure controls</li> <li>Appropriate engineering contrasting to the second second</li></ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work.
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 nn Long-term value: 1450 nn Carc (if more than 0.1%)</li> <li>Additional information: The lite</li> <li>8.2 Exposure controls</li> <li>Appropriate engineering controls</li> <li>Appropriate engineering controls</li> <li>General protection measures</li> <li>General protective and hygients</li> <li>Wash hands before breaks and Do not inhale gases / fumes / action</li> <li>Respiratory protection: Use sures</li> <li>Hand protection Not required.</li> </ul>	hat require monitoring at the workplace: mg/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation.
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 m Long-term value: 1450 m Carc (if more than 0.1%)</li> <li>Additional information: The limit of the second second</li></ul>	hat require monitoring at the workplace: mg/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation.
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 m Long-term value: 1450 m Carc (if more than 0.1%)</li> <li>Additional information: The limit of the second second</li></ul>	hat require monitoring at the workplace: mg/m <sup>3</sup> , 750 ppm gg/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res prial
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 m Long-term value: 1450 m Carc (if more than 0.1%)</li> <li>Additional information: The limit value of the second second</li></ul>	hat require monitoring at the workplace: mg/m <sup>3</sup> , 750 ppm gg/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res prial
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 metal Long-term value: 1450 metal Carc (if more than 0.1%)</li> <li>Additional information: The limit value and the engineering controls</li> <li>Appropriate engineering controls</li> <li>Appropriate engineering controls</li> <li>General protection measure of the engineering of</li></ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to a
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 me Long-term value: 1450 me Carc (if more than 0.1%)</li> <li>Additional information: The limit value of the second secon</li></ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to a
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 me Long-term value: 1450 me Carc (if more than 0.1%)</li> <li>Additional information: The limit value of the second secon</li></ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to a ed.
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 ne Long-term value: 1450 ne Carc (if more than 0.1%)</li> <li>Additional information: The lite of the controls</li> <li>Additional information: The lite of the controls</li> <li>Appropriate engineering controls</li> <li>Appropriate engineering controls</li> <li>General protection measures</li> <li>General protection because and hygients</li> <li>Wash hands before breaks and Do not inhale gases / fumes / and protection. Use su</li> <li>Hand protection Not required.</li> <li>Material of gloves Rubber glove matter the exact break trough time he observed.</li> <li>Eye/face protection Not required.</li> </ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to a ed. d chemical properties
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 ne Long-term value: 1450 ne Carc (if more than 0.1%)</li> <li>Additional information: The limit value of the</li></ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to be ed. d chemical properties
<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values the 106-97-8 butane, pure</li> <li>WEL Short-term value: 1810 ne Long-term value: 1450 ne Carc (if more than 0.1%)</li> <li>Additional information: The lite of the controls</li> <li>Additional information: The lite of the controls</li> <li>Appropriate engineering controls</li> <li>Appropriate engineering controls</li> <li>General protection measures</li> <li>General protection because and hygients</li> <li>Wash hands before breaks and Do not inhale gases / fumes / and protection. Use su</li> <li>Hand protection Not required.</li> <li>Material of gloves Rubber glove matter the exact break trough time he observed.</li> <li>Eye/face protection Not required.</li> </ul>	hat require monitoring at the workplace: ng/m <sup>3</sup> , 750 ppm ng/m <sup>3</sup> , 600 ppm of buta-1.3-diene) sts valid during the making were used as basis. ols No further data; see item 7. s, such as personal protective equipment ic measures: at the end of work. erosols. itable respiratory protective device in case of insufficient ventilation. res trial as to be found out by the manufacturer of the protective gloves and has to i ed. d chemical properties

*Page 4/8* 

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Revision: 20.12.2022

Trade name: tapi-foam

	(Contd. of page
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	<0 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.5 Vol %
Upper:	8.5 Vol %
Flash point:	<-20 °C
Ignition temperature:	354 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Parthy missible
	Partly miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	2,100 hPa
Density and/or relative density	
Density at 20 °C:	$0.95 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Form: Important information on protection of health and	Aerosol d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Not determined.
Solvent separation test:	15.0 %
Solvent separation test: Organic solvents:	15.0 % 73.0 %
Solvent separation test: Organic solvents: Water:	15.0 % 73.0 %
Solvent separation test: Organic solvents: Water: Change in condition	73.0 %
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate	73.0 % Not applicable.
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe	73.0 % Not applicable.
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate	73.0 % Not applicable. So Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	73.0 % Not applicable. <b>25</b> Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe	73.0 % Not applicable. <b>25</b> Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	73.0 % Not applicable. <b>'s</b> Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	73.0 % Not applicable. S Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases	73.0 % Not applicable. S Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases	73.0 % Not applicable. S Void Void Void Void Extremely flammable aerosol. Pressurised contained
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols	73.0 % Not applicable. Void Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases	73.0 % Not applicable. Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases	73.0 % Not applicable. Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols	73.0 % Not applicable.
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	73.0 % Not applicable. <b>v</b> Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases	73.0 % Not applicable. S Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	73.0 % Not applicable. S Void Void Void Extremely flammable aerosol. Pressurised containen May burst if heated. Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	73.0 % Not applicable. S Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	73.0 % Not applicable. S Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void Void Void Void Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids	73.0 % Not applicable. S Void Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void
Solvent separation test: Organic solvents: Water: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	73.0 % Not applicable. S Void Void Void Extremely flammable aerosol. Pressurised container May burst if heated. Void

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Revision: 20.12.2022

Trade name: tapi-foam

		(Contd. of page 4)
· Pyrophoric liquids	Void	
	Void	
· Pyrophoric solids	Void	
	Void	
• Self-heating substances and mixtures	Void	
<i>,</i>	Void	
• Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
ů –	Void	
· Oxidising liquids	Void	
0	Void	
· Oxidising solids	Void	
8	Void	
· Organic peroxides	Void	
0 1	Void	
· Corrosive to metals	Void	
	Void	
· Desensitised explosives	Void	
······	Void	

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

 $\cdot$  **10.5 Incompatible materials:** No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (Rat)

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.* 

• STOT-single exposure Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

• 11.2 Information on other hazards

• *Endocrine disrupting properties* None of the ingredients is listed.

(Contd. on page 6)

GE

Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

*Version number 31 (replaces version 30)* 

Printing date 20.12.2022

Revision: 20.12.2022

#### Trade name: tapi-foam

(Contd. of page 5)

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.* 

# **SECTION 14: Transport information** · 14.1 UN number or ID number · ADR, IMDG, IATA UN1950 • 14.2 UN proper shipping name ·ADR 1950 AEROSOLS · IMDG, IATA AEROSOLS · 14.3 Transport hazard class(es) ·ADR 2 5F Gases. · Class · Label 2.1 (Contd. on page 7)

Page 7/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Trade name: tapi-foam

	(Contd. of pag
· IMDG, IATA	
· Class	2 Gases.
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· Marine pollutant:	JA
· 14.6 Special precautions for user	Warning: Gases.
• Hazard identification number (Kemler code):	23
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Catego
	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
• 14.7 Maritime transport in bulk according to IM instruments	<i>Not applicable.</i>
· Transport/Additional information:	
· ADR	
· ADK · Limited quantities (LQ)	11.
· Excepted quantities (EQ)	Code: E0
Encepten quantines (DZ)	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E0
1 - 1 - ( 2)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2022

Version number 31 (replaces version 30)

Revision: 20.12.2022

Trade name: tapi-foam

	(Contd. of page 7)
• Regulation (EC) No 648/2004 on detergents / Labelling for contents	
aliphatic hydrocarbons	≥15 - <30%
anionic surfactants	<5%
<b>15.2 Chemical safety assessment:</b> A Chemical Safety Assessment has not been carried out.	

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- May be fatal if swallowed and enters airways. H304
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronvms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• \* Data compared to the previous version altered.